

10/17/03
17231 U.S. PTO

22141 U.S. PTO
10/688523
101703

UNITED STATES PATENT APPLICATION

Rail Positioning Device For Retractable Bumper Assembly

Be it known that I, Will Heddon, a citizen of the United States of America and a resident of Lake Wales in the State of Florida, have invented new and useful improvements in the above entitled invention the following of which is a specification in full, clear and exact terms to enable one skilled in the art to make and use the same.

BACKGROUND OF THE INVENTION

Field of the Invention

A rail positioning device for use with a retractable bumper assembly to prevent bowling balls from entering a gutter adjacent the retractable bumper
5 assembly.

Description of the Prior Art

A poorly thrown bowling ball can fall into either gutter. For various reasons bumper systems have been developed that prevent a bowling ball from entering the gutters. Generally, an elongated guard or rail is placed along the length of each
10 gutter to prevent a bowling ball from entering the corresponding gutter.

Numerous retractable bumper systems have been developed which permit the elongated guards or rails to be easily deployed or retracted. There are several problems associated with these various systems including:

- The attaching means at the pivot connection between the rail and the
15 support members normally consist of a mechanical fastener that is exposed to view.
- The pivots are rigidly mechanically attached to the rail making the pivots vulnerable to ball impact, which in turn causes damage to the pivots.
- Some rail materials expand and contract with moisture and/or
20 temperature changes. This causes undue stress on the rails and pivot arms.

- Assembly is required on all the known rail pivot combinations prior to packaging and shipping which adds to the cost of shipping, labor and overhead.

- 25
- Exposed fasteners sometimes come loose and cause ball damage.
 - Excessive ball speed impact damages rails and pivot arms that must be replaced prior additional use. Replacement is time consuming and expensive and normally involves both the rail and multiple pivot arms.

U.S. 6,402,629 describes a bumper system to prevent a bowling ball from

30 entering the gutters, redirecting the ball into the lane comprising a longitudinal rail with a plurality of pivot arms affixed thereto. The pivot arms are pivotally affixed to the lane bed such that when the bumper system is in a retracted position the horizontal surface of the longitudinal rails are in a substantially abutting relation to the side of the lane, and the adjacent gutters are adapted to receive any balls that

35 are bowled towards either side of the lane, directing the balls to the end of the lane, missing the pin deck. In an extended position, the longitudinal rails prevent balls from entering the adjacent gutters redirecting balls into the lane such that the balls strike the pins in the pin deck.

U.S. 5,380,251 discloses a bowling alley bumper system to selectively guard

40 against a bowling ball rolling into a gutter comprising a bungee cord extends along each side edge of a bowling alley lane. When the bungee cord is and in a first position below the lane surface bowling balls can roll into a gutter. A lifting mechanism can raise the bungee cord to a position above the lane surface for receiving bowling balls rolling on the surface toward the gutter and redirecting the

45 bowling balls toward the center of the lane and away from the gutter. The bungee cord is lifted to its second position by a plurality of elongated rods positioned to move alongside the lane below the gutter surface. A connecting rod raises and lowers the elongated rods through a lever action thereby positioning the bungee cord at its first stored position or its elevated position for guarding the gutter.

50 Additional examples of such retractable bumper systems have been described in: U.S. 4,420,155; U.S. 4,792,136; U.S. 4,900,024; U.S. 5,181,716; U.S. 5,207,422; U.S. 5,304,097; U.S. 5,322,476; U.S. 5,358,448; U.S. 45,405,295; U.S. 5,415,591; U.S. 5,417,616; U.S. 5,435,788; U.S. RE. 35,232; U.S. 5,564,986; U.S. 5,681,224; U.S. 5,800,274 and U.S. 5,857,918.

SUMMARY OF THE INVENTION

The present invention relates to a rail positioning device to selectively position a retractable bumper assembly to prevent a bowling ball from the bowling lane gutter adjacent thereto. The retractable bumper assembly comprises an elongated rail
5 movable between a retracted position and an elevated position supported by a plurality of rail support members.

The rail positioning device comprises a rail positioning assembly and a rail positioning actuator. The rail positioning assembly includes a rail positioning member longitudinally movable between a retracted position and an extended position and a
10 rail positioning element rotatably movable between a retracted position and an extended position disposed to engage the elongated rail. The rail positioning actuator includes an actuator element longitudinally movable between a retracted and an extended position to selectively move the rail positioning member from the retractable and the extended position which, in turn, moves the rail positioning
15 element from the retracted position and the extended position as the actuator element moves from the retracted position to the extended position to move the elongated rail from the retracted position to the elevated position to prevent a bowling ball from entering the adjacent gutter.

The actuator element can be displaced or moved between the retracted
20 position and the extended position by a mechanical, electrical, hydraulic or pneumatic displacement system, and will be readily apparent to the skilled artisan.

The invention accordingly comprises the features of construction, combination of elements, and arrangement of parts that will be exemplified in the construction hereinafter set forth, and the scope of the invention will be indicated in the claims.

BRIEF DESCRIPTION OF THE DRAWINGS

For a fuller understanding of the nature and object of the invention, reference should be had to the following detailed description taken in connection with the accompanying drawings in which:

5 Figure 1 is a perspective view of the rail positioning device of the present invention in the extended position.

 Figure 2 is a side view of the rail positioning device of the present invention in the extended position.

 Figure 3 is a side view of the rail positioning device of the present invention in
10 the retracted position.

 Figure 4 is a top view of the rail positioning device of the present invention in the retracted position.

 Figure 5 is a detailed end view of the rail positioning device of the present invention in the extended position.

15 Similar reference characters refer to similar parts throughout the several views of the drawings.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

As shown in FIGS. 1 through 5, the present invention relates to a rail positioning device generally indicated as 10 for use with a retractable bumper assembly generally indicated as 12 that includes an elongated rail 14 movable
5 between a retracted position and an elevated position supported by a plurality of rail support members each indicated as 16 (FIG. 1) to prevent bowling balls from entering a bowling lane gutter (not shown) adjacent the retractable bumper assembly 12 when the elongated rail 14 is in the elevated position.

The rail positioning device 10 comprises a rail positioning assembly generally
10 indicated as 18 and a rail positioning actuator generally indicated as 20 mounted on or coupled to a rail support generally indicated as 22 such as an L-shape member including a substantially horizontal element or leg 24 and a substantially vertical element or leg 26 to secure the rail positioning device 10 and the retractable bumper assembly 12 adjacent the bowling lane gutter (not shown) by a plurality of fasteners
15 27.

The rail positioning assembly 18 comprises a rail positioning member 28 longitudinally movable between an extended position (FIG. 2) and a retracted position (FIG. 3) and a rail positioning element 30 rotatably movable between an extended position (FIG. 2) and a retracted position (FIG. 3). The rail positioning
20 member 28 includes an arcuate or convex camming surface 32 disposed to engage the side surface 34 of the rail positioning element 30 and an inclined substantially flat surface 36 disposed to engage the side surface 34 of the rail positioning element 30 when the rail positioning member 28 and the rail positioning element 30 are each in

the extended position to maintain the elongated rail 14 in the elevated position. The
25 lower surface of the rail positioning member 28 slidably engages the substantially
horizontal element or leg 24 of the rail support 22 during operation of the rail
positioning device 10. The rail positioning element 30 includes an upper arcuate or
convex camming surface 38 to engage the elongated rail 14 of the retractable
bumper assembly 12. The rail positioning element 30 is rotatably coupled to the
30 substantially vertical element or leg 26 of the rail support 22 by a fastener generally
indicated as 40.

The rail positioning actuator 20 comprises an actuator element generally
indicated as 42 longitudinally movable between an extended position (FIG. 2) and a
retracted position (FIG. 3) and an actuator element positioning device generally
35 indicated as 44 to move the actuator element 42 between the extended position and
the retracted position.

The rail positioning actuator 20 can be displaced or moved between the
retracted position and the extended position by a mechanical, electrical, hydraulic or
pneumatic displacement system, and will be readily apparent to the skilled artisan.
40 For example, the actuator element 42 may include an elongated shaft 46 having one
end portion thereof coupled to the rail positioning member 28 of the rail positioning
assembly 18 and an actuator member or piston 48 coupled to the opposite end
portion thereof; while, the actuator element positioning device 44 may comprise a
hydraulic or pneumatic cylinder 50 coupled to a fluid pressure source.

45 Operation of the actuator element positioning device 44 involves the selective
introduction of high pressure air or hydraulic fluid into the hydraulic or pneumatic

cylinder 50 pushing against the actuator member or piston 48 to extend or retract the elongated shaft or connecting rod 46 extending or retracting the rail positioning member 28. Pressurized air or hydraulic fluid is circulated through the hydraulic or pneumatic cylinder 50 by a supply conduit 52 and a return conduit 54 in operative communication with a hydraulic pump or pressurized air supply 56. The hydraulic pump or pressurized air supply 56 may be powered by an electric motor. Electromechanical valves (not shown) common in the art are disposed between the supply conduit 52 and the return conduit 54 and the hydraulic pump or pressurized air supply 56 to control the flow of air or hydraulic fluid to and from the hydraulic or pneumatic cylinder 50.

The effective length of the elongated shaft or connecting rod 46 can be adjusted by an adjustment device generally indicated as 58 such as a nut threadably mounted on an externally threaded portion of the elongated shaft 46.

As shown in FIG. 1, each rail support member 16 is pivotally coupled to the substantially vertical element or leg 26 of the rail support 22 by a corresponding pin 59 or the like extending through a corresponding aperture 60; while, the opposite end portion of each rail support member 16 is rotatably coupled to the elongated rail 14 by corresponding pins or members 62.

In operation, the rail positioning member 28 is moved from the retractable and the extended position by the actuator element 42 moving longitudinally from the retracted position to the extended position to rotate the rail positioning element 30 from the retractable and extended position to move the elongated rail 14 from the

retracted position to the elevated position to prevent a bowling ball from entering the
70 adjacent gutter (not shown).

The process is reversed to return the elongated rail 14 to the retracted position. Since the rail positioning element 30 is supported by the rail positioning member 28 inclined at an angle of less than 90 degrees (90°), the rail positioning element 30 rotates downwards under the force of gravity as the rail positioning
75 member 28 is retracted by the actuator element 42.

It will thus be seen that the objects set forth above, among those made apparent from the preceding description are efficiently attained and since certain changes may be made in the above construction without departing from the scope of the invention, it is intended that all matter contained in the above description or
80 shown in the accompanying drawing shall be interpreted as illustrative and not in a limiting sense.

It is also to be understood that the following claims are intended to cover all of the generic and specific features of the invention herein described, and all statements of the scope of the invention that, as a matter of language, might be said
85 to fall therebetween.

Now that the invention has been described,